

**Series 3730**  
**Type 3730-4 Electropneumatic Positioner**  
 with PROFIBUS PA communication



Device			Indicating and operating modules							
Model Index	Firmware K <sup>1</sup> / R <sup>2</sup>	Device Rev	PA Profile	TROVIS-VIEW	Siemens PDM <sup>3</sup>	DTM (FDT 1.2)				
00	K 1.00 – 1.10 R 1.43 – 1.44	1	3.01	≥ 3.22	≥ 5.1 ≥ 6.0 <sup>6</sup>	≥ 1.3.0				
01	K 1.11 – 1.17 R 1.45 – 1.46	2	3.01	≥ 3.40	≥ 5.1 ≥ 6.0 <sup>6,12</sup>	≥ 1.3.0				
01	K2.00 R1.52	3	3.02	≥ 4.00	≥ 6.0 <sup>6</sup>	≥ 1.3.0				

<sup>1</sup> Communication firmware

<sup>2</sup> Control firmware

<sup>3</sup> Device is subsequently added to PDM using the "device install" / "manage device catalog" function (available at [www.samsongroup.com](http://www.samsongroup.com))

<sup>6</sup> With enhanced DD (EDD)

<sup>12</sup> K1.11 DD Revision 2 and higher